

SIAG/OPT Views-and-News

A Forum for the SIAM Activity Group on Optimization

Volume 21 Number 2

December 2010

Contents

Environmental Optimization

<i>Oil Spill Response Planning with MINLP</i>	
Fengqi You and Sven Leyffer	1
Bulletin	9
Comments from the Editor	
Sven Leyffer	9
Chairman's Column	
Michael C. Ferris	10

[3, 13, 19]. Yet significant interactions between them exist throughout the response. Oil-spill cleanup activities change the volume and area of the oil slick and in turn affect the oil transport and weathering process, which also affects coastal protection activities and cleanup operations (e.g., performance degradation and operational window of cleanup facilities). Therefore, it is critical to integrate the response planning model with the oil transport and weathering model.

Environmental Optimization

Oil Spill Response Planning with MINLP

Fengqi You and Sven Leyffer

Argonne National Laboratory

9700 South Cass Avenue, Argonne, Illinois 60439, USA

(youf@mcs.anl.gov, leyffer@mcs.anl.gov).

1. Introduction

Catastrophic oil spills [10], such as the recent Deepwater BP oil spill in the Gulf of Mexico [20], have demonstrated the importance of developing responsive and effective oil spill response planning strategies for the oil industry and the government. Although a few models have been developed for oil-spill response planning, response operations and the oil weathering process are usually considered separately

The objective of this note is to develop an optimization approach that seamlessly integrates the planning of oil-spill response operations with the oil transport and weathering process. A mixed-integer dynamic optimization (MIDO) model is proposed that simultaneously predicts the time trajectories of the oil volume and slick area and the optimal response cleanup schedule and coastal protection plan. The model takes into account the time-dependent oil physiochemical properties, spilled amount, hydrodynamics, weather conditions, facility availability, performance degradation, cleanup operational window, and regulatory constraints. To solve the MIDO problem, we reformulate it as a mixed-integer nonlinear programming (MINLP) problem using orthogonal collocation on finite elements. We also develop a mixed-integer linear programming (MILP) model to obtain a good starting point for solving the nonconvex MINLP problem. The application of the proposed integrated optimization approach is illustrated through a case study based on the Deepwater BP oil spill.

The rest of this paper is organized as follows. Section 2 presents the problem statement. The detailed model formulation is given in Section 3. In Section 4, we present computational results for the case study.

2. Problem Statement

The problem addressed in this work can be formally stated as follows. An oil spill occurs at a specific location. The initial spill volume, constant release rate, and release duration are all known. We are also given the physical and chemical parameters of the oil and seawater, as well as the weather data, such as wind speed and temperature. There is a set of staging areas $i \in I$ along the shoreline near the spill site. Because of spreading and drift processes, the oil slick may hit the coast around staging area i at time t if the slick area is larger than $\overline{area}_{i,t}$, which is a given parameter in this work and can be derived from the drift process based on weather and sea conditions. A minimum length of boom \underline{L}_i should be deployed in staging area i before the oil slick hits the corresponding coast. The maximum boom deployment rates and the unit boom deployment cost are given. Booms deployed around staging area i will be subject to failure after a lifetime φ_i . The major cleanup methods include mechanical cleanup and recovery (skimming), in situ burning, and chemical dispersant application; and the corresponding cleanup facilities are indexed by m , b , and d , respectively. The maximum number of each type of cleanup facility in each staging area and the corresponding total response time are known. The operating capacities of the cleanup facilities and the corresponding operational costs and operating conditions, as well as the time-dependent weather factors, are given. When the response operations finish, the volume of oil remaining on the sea surface should not exceed the cleanup target \underline{V} . The problem is to simultaneously determine the coastal protection plan and cleanup schedule in order to minimize the total response cost under a specific response time span.

3. Mixed-Integer Dynamic Optimization Model

The proposed MIDO model has an objective function to minimize the total response cost, and includes a set of ordinary differential equations (ODEs) that model the oil transport and weathering process and a set of mixed-integer constraints for response planning. The oil weathering model uses a continuous-time representation, while in the planning model we

discretize the planning horizon into $|T|$ time periods with H_t as the length of time period $t \in T$. This is consistent with the real-world practice that most response decisions are made on an hourly or daily basis. The integration of these two time representations will be discussed at the end of this section.

3.1 Oil Transport and Weathering Model

Prediction of the oil transport and weathering process needs to account for many factors, such as oil properties, spilled amount, hydrodynamics, and weather conditions, and to consider a variety of complex physicochemical processes taking place simultaneously. Over 50 oil weathering models, based on empirical and semi-empirical approaches, have been developed. Although any oil weathering model can, in principle, be used in the approach proposed in this paper, we employ a dynamic mathematical model taking into account the dominant processes (spreading, evaporation, emulsification, and dispersion) that cause significant short-term changes in oil characteristics. We note that a PDE model might better capture the physiochemical evolution of oil slick in the three dimensional space. However, such a PDE constraint would result in an MINLP that is orders of magnitude beyond the current solver capabilities, and would be challenging to be integrated with the response planning model. Thus, we consider only the time variation in area, volume and other important physiochemical parameters, and model the effect of wind and current through parameters with constant values.

Spreading, which strongly influences coastal protection operations and other weathering processes, is probably the most dominant process of a spill. The rate of change of slick area is given by [8, 12, 22]:

$$\frac{dA(t)}{dt} = K_1 A^{-1}(t) V^{3/4}(t) - W(t) \frac{A(t)}{V(t)}, \quad (1)$$

where $A(t)$ is the surface area of oil slick (m^2), $V(t)$ is the volume of oil (m^3), and K_1 is the physicochemical parameters of the crude oil with a default value, and $W(t)$ is the cleanup rate given in Equation (3). The first term on the right-hand side of Equation (1) models the natural spreading process. The second term refers to the reduction of slick area as a result of cleanup operations. The initial volume

of the oil slick is given as $V(0) = V_0$. The initial area of oil slick can be determined by the well-known gravity-viscous formulation [6]:

$$A(0) = \pi \cdot \frac{k_2^4}{k_3^2} \left[\frac{(\rho_w - \rho_o)V_0^5 g}{\rho_w \nu_w} \right]^{1/6},$$

where g is the acceleration of gravity, ρ_w is seawater density, ρ_o is the density of fresh oil, ν_w is the kinematic viscosity of seawater, V_0 is the initial volume, and k_2 and k_3 are empirical constants.

The volume balance of the oil slick is based on the volume variation rate given as follows [15, 22]:

$$\frac{dV(t)}{dt} = -V(t) \frac{dF_E(t)}{dt} - \frac{dV_D(t)}{dt} - W(t) + R(t),$$

where the first term on the right-hand side models the evaporation loss, the second term describes natural dispersion, the third term is the cleanup rate, and the last term is the oil spill rate given as follows:

$$R(t) = \begin{cases} \text{constant spill rate,} & 0 \leq t \leq t_s \\ 0, & t_s \leq t \leq t_f, \end{cases}$$

where t_s is the time when the oil spillage stops and t_f is the final time of the planning horizon (response time span). The remaining volume of oil at the end of the response time span should not exceed the cleanup target,

$$V(t_f) \leq \underline{V}.$$

Evaporation is the primary initial process involved in the removal of oil from sea. The rate that oil evaporates from the sea surface is modeled by the following equation [17]:

$$\frac{dF_E(t)}{dt} = \frac{K_{ev}A(t)}{V(t)} \exp \left[A_{ev} - \frac{B_{ev}}{T_K} (T_0 + T_G F_E(t)) \right],$$

where $F_E(t)$ is the volume fraction of oil that has evaporated, T_K is the oil temperature (K), which is assumed to be a constant, K_{ev} is the mass transfer coefficient for evaporation, T_0 is the initial boiling point, T_G is the gradient of the oil distillation curve, and A_{ev} and B_{ev} are empirical constants. Because no oil has evaporated at time 0, the initial value of evaporative fraction is given by $F_E(0) = 0$.

The rate of dispersion into the water column of the floating oil slick is given by the following equation [8, 12, 15]:

$$\frac{dV_D(t)}{dt} = \frac{0.11 \cdot (S_w + 1)^2 \cdot A(t)V(t)}{A(t) + 50\zeta \cdot V(t)\mu^{1/2}(t)},$$

where $V_D(t)$ is volume of oil naturally dispersed, S_w is the wind speed, and ζ is the oil-water interfacial tension. The initial value of the volume of oil that is naturally dispersed is zero, i.e. $V_D(0) = 0$.

In emulsification, water droplets are entrained in the oil. The dynamic emulsification process that incorporates water into oil can be computed with the following equation [8]:

$$Y_W(t) = C_3 \left[1 - \exp \left(- \frac{K_{em}}{C_3} (S_w + 1)^2 \cdot t \right) \right], \quad (2)$$

where $Y_W(t)$ is the fractional water content in the emulsion, C_3 is a viscosity constant for the final fractional water content, K_{em} is an empirical constant and t is the time in seconds.

As a result of both Mousse formation and evaporation, the viscosity of oil slick may significantly increase during the emulsification process. The rate of changes in viscosity is given by [4, 15]:

$$\frac{d\mu(t)}{dt} = \frac{2.5\mu(t)}{(1 - C_3 Y_W(t))^2} \frac{dY_W(t)}{dt} + C_4 \mu(t) \frac{dF_E(t)}{dt},$$

where $\mu(t)$ is the viscosity of the oil and C_4 is an oil-dependent constant. The initial value of the viscosity is the same as the parent oil's viscosity, which can be calculated by the following equation [4]:

$$\mu(0) = 224 \times \sqrt{AC},$$

where AC is the asphaltene content of the parent oil.

3.2 Response Planning Constraints

We consider both coastal protection and oil-spill cleanup operations in the response. The major coastal protection method is to deploy booms to prevent the oil from spreading to the shore. Three major oil spill cleanup methods are mechanical cleanup and recovery, in situ burning, and chemical dispersants. Mechanical systems can skim the oil slick and recover oil from the emulsion; in situ burning and chemical dispersants remove oil only from the surface of the sea. Reviews of oil spill response methods and equipment are given in [18, 22].

In order to protect sensitive shorelines, either the slick area must be controlled through effective cleanup operations, or coastal protection booms must be deployed with sufficient lengths around the

staging areas before they are hit by the oil slick. It can be modeled with the following constraint:

$$A(t) \leq \overline{area}_{i,t} + A^U \cdot z_{i,t}, \quad \forall i \in I, t \in T,$$

where $z_{i,t}$ is a binary variable that equals 1 if sufficient booms have been deployed to protect the shoreline around staging area i at time t , A^U is the upper bound of oil slick area, and $\overline{area}_{i,t}$ is a given parameter for the area of the oil slick that will hit the shore around staging area i at time period t . $\overline{area}_{i,t}$ depends primarily on the drift process, which relates to the wind speed and direction [22].

The shoreline around staging area i is fully protected by the booms at time period t if and only if the length of boom is no less than the required length. So we have:

$$\underline{L}_i \cdot z_{i,t} \leq bl_{i,t} \leq \underline{L}_i + L^U \cdot z_{i,t}, \quad \forall i \in I, t \in T,$$

where \underline{L}_i is the length of boom required to protect the coast around staging area i and $bl_{i,t}$ is the length of boom deployed along the shore of staging area i at the end of time period t .

Because of currents and winds, conventional booms are subject to damages over time. Coastal protection booms deployed at staging area i can be effective for only a certain lifetime φ_i after deployment. Booms deployed at time $t - \varphi_i$ will fail at time t [11]. Thus, the length of the boom around the shore of staging area i at the end of time period t ($bl_{i,t}$) is equal to the boom length at the end of the previous time period ($bl_{i,t-1}$) plus the length of the boom deployed at the current time period ($bdep_{i,t}$) minus those that fail at this time period ($bdep_{i,t-\varphi_i}$). Thus, the balance of boom length is given as follows.

$$bl_{i,t} = bl_{i,t-1} + bdep_{i,t} - bdep_{i,t-\varphi_i}, \quad \forall i \in I, t \in T.$$

The length of boom deployed along the shoreline near staging area i at time t should not exceed the maximum deployment rates ($BDU_{i,t}$) times the length of time period t (H_t). Thus, we have:

$$0 \leq bdep_{i,t} \leq BDU_{i,t} \cdot H_t, \quad \forall i \in I, t \in T.$$

We define $x_{i,m,t}^M$ as the number of mechanical cleanup and recovery systems type m from staging

area i operating at time period t . It should not exceed the corresponding available number ($N_{i,m,t}^M$).

$$0 \leq x_{i,m,t}^M \leq N_{i,m,t}^M, \quad \forall i \in I, m \in M, t \in T.$$

The volume of oil cleaned and recovered from the sea surface with mechanical systems at time period t (W_t^M) is given by the following equation [3].

$$W_t^M = \sum_i \sum_m (1 - Y_W(t)) \cdot H_t \cdot \omega_t^M \cdot Q_{i,m}^M \cdot x_{i,m,t}^M, \quad \forall t \in T,$$

where $Q_{i,m}^M$ is the operating capability of mechanical system m from staging area i ; ω_t^M is the weather factor (between 0 and 1), which can be determined from weather forecasting; and $Y_W(t)$ is the fractional water content defined in (2).

In situ burning response system b can operate only when the oil slick (δ_t) is thicker than δ_b^B , see [7]. We introduce a binary variable ($xx_{b,t}^B$) to model this restriction through the following constraint:

$$\delta_b^B \cdot xx_{b,t}^B \leq \delta(t) \leq \delta_b^B + \delta^U \cdot xx_{b,t}^B,$$

where δ^U is the upper bound of the slick thickness and $\delta(t)$ is the thickness of the oil slick given by:

$$\delta(t) \cdot A(t) = V(t).$$

For in situ burning response systems, the availability constraints are given as follows:

$$x_{i,b,t}^B \leq N_{i,b,t}^B \cdot xx_{b,t}^B, \quad \forall i \in I, b \in B, t \in T,$$

where $x_{i,b,t}^B$ is the number of in situ burning systems b from staging area i operating at time period t , and $N_{i,b,t}^B$ is the availability in staging area i .

The volume of oil burned at time period t (W_t^B) is given by the following equation:

$$W_t^B = \sum_i \sum_b H_t \cdot \omega_t^B \cdot Q_{i,b}^B \cdot x_{i,b,t}^B, \quad \forall t \in T,$$

where $Q_{i,b}^B$ is the operating capability of in situ burning system b from staging area i and ω_t^B is the weather factor for in situ burning at time t .

The availability constraint of chemical dispersant application systems is given by:

$$x_{i,d,t}^D \leq N_{i,d,t}^D \cdot \gamma_{i,d,t} \cdot H_t, \quad \forall i \in I, d \in D, t \in T,$$

where $x_{i,d,t}^D$ is the number of sorties of chemical dispersant application systems d dispatched from staging area i at time period t , $N_{i,d,t}^D$ is the corresponding availability, and $\gamma_{i,d,t}$ is the maximum number of sorties of dispersant application systems d from staging area i to spray dispersant on the oil slick at time period t . Note that the maximum number of sorties depends on the type of dispersant application system (e.g., a helicopter may operate 10 sorties per day for an offshore oil spill 100 miles away) [9].

The volume of oil removed from the sea surface by using chemical dispersants at time period t (W_t^D) is given by the following equation:

$$W_t^D = \sum_i \sum_d \omega_t^D \cdot \rho_t^{eff} \cdot \rho_d^{acc} \cdot Q_{i,d}^D \cdot x_{i,d,t}^D, \quad \forall t \in T$$

where $Q_{i,d}^D$ is the operating capacity of dispersant application systems d from staging area i , ω_t^D is the corresponding weather factor, ρ_t^{eff} is the effectiveness factor (ratio between oil dispersed and dispersant sprayed) for chemical dispersant application at time t , and ρ_d^{acc} is the accuracy factor (percentage of sprayed dispersant falls on the oil slick) of dispersant application systems d .

The total amount of chemical dispersant used throughout the entire response operation should not exceed the limit set by the regulator (D_{limit}) [9].

$$\sum_i \sum_d Q_{i,d}^D \cdot x_{i,d,t}^D \leq D_{limit}$$

We model the real-time cleanup rate ($W(t)$) as a piece-wise step function as follows:

$$W(t) \cdot H_t = W_t^M + W_t^B + W_t^D. \quad (3)$$

In addition, the decisions variables of this model must satisfy the following integrality and nonnegativity constraints:

$$\begin{aligned} Z_{i,t} &\in \{0, 1\} \\ x_{i,m,t}^M, x_{i,b,t}^B, x_{i,d,t}^D &\in \{0\} \cup Z^+ \\ bdep_{i,t}, bl_{i,t}, W_t^M, W_t^B, W_t^D &\geq 0 \\ V(t), A(t), F_E(t), V_D(t), Y_W(t), \mu(t), \delta(t) &\geq 0. \end{aligned}$$

3.3 Objective Function

The objective function is to minimize the total response cost, given as follows.

$$\min : \quad TotalCost = \sum_i \sum_m \sum_t C_{i,m,t}^M \cdot x_{i,m,t}^M$$



Figure 1: Oil spill site and locations of the three staging areas for the case study

$$\begin{aligned} &+ \sum_i \sum_b \sum_t C_{i,b,t}^B \cdot x_{i,b,t}^B \\ &+ \sum_i \sum_d \sum_t C_{i,d,t}^D \cdot x_{i,d,t}^D \\ &+ \sum_i \sum_t C_{i,t}^{boom} \cdot bdep_{i,t} \\ &- \sum_t P_0 \cdot W_t^M, \end{aligned}$$

where $C_{i,m,t}^M$, $C_{i,b,t}^B$ and $x_{i,d,t}^D$ are unit operating cost of mechanical cleanup and recovery system, in situ burning system and chemical dispersant application system, respectively, $C_{i,t}^{boom}$ is the cost of deploying unit length of coastal protection boom around staging area i , and P_0 is the unit price of recovered oil. In the objective function, the first three terms are the cost of the cleanup operations, the fourth terms is the cost of coastal protection operations, and the last term is the credit resulting from the recovery of the emulsified oil.

3.4 Solution Approach

The resulting model is an MIDO, which can be solved by a number of approaches [1, 2, 5, 14]. Because of the problem size and structure, in this work we use a simultaneous approach in order to integrate the continuous-time representation in the oil weathering model and the discrete time representation in the planning model. In the simultaneous approach, the MIDO model is fully discretized based on orthog-

onal collocation on finite elements and then is reformulated into an equivalent MINLP problem. First, the entire planning horizon is divided into a number of finite elements. Within each finite element an adequate number of internal collocation points is selected. Using several finite elements is useful to represent dynamic profiles with nonsmooth variations. Thus, the differential and algebraic variable profiles are approximated at each collocation point by using a family of interpolation polynomials. To integrate the continuous- and discrete-time representations, we consider one time period as a finite element in the discretization process. In this way, the index t represents not only the discrete time periods but also the finite elements, and the length of finite element t is the same as the length of the corresponding time period (H_t).

Our discretization does not take into account the possibility of drastically different rates of the differential variables. In this case, it may become necessary to decouple the problem in time using a quasi-steady-state assumption [16]. Our goal here is to present an approach that couples the ODE with the planning model.

The reformulated MINLP is highly nonlinear and nonconvex, and requires careful initializations to avoid numerical difficulties. To obtain a “good” starting point, we use the MILP model given in [21, 22] for initialization. The approximate MILP model, which is obtained by decoupling the ODE from the discrete-time response planning model, implicitly considers the oil weathering process in the response planning by assuming the time trajectory of the slick thickness is not affected by response operations.

4. Case Study

Our case study is based on the *Deepwater Horizon BP* oil spill in the Gulf of Mexico. There are three major staging areas for the response operations: S1, S2, and S3. Their locations, along with the spill site, are given in the map in Figure 1. The minimum distances between the three staging areas and the oil spill site are 60 kilometers, 120 kilometers, and 180 kilometers, respectively. In this case, we assume the oil slick drifts toward the shore as a result of wind and current directions. The lengths of the booms required to protect the sensitive coastline




Figure 2: Time trajectories of the oil volumes removed by three methods and remaining on the sea surface

near the three staging areas are 200 kilometers, 180 kilometers, and 300 kilometers, respectively. The spilled oil is considered as crude oil with an API degree of 25. The initial spill amount is $10,000 \text{ m}^3$, and the oil releases continue for 42 days with a constant rate of $10,000 \text{ m}^3/\text{day}$. The cleanup target is that no more than $1,500 \text{ m}^3$ of oil remain on the sea surface after the response. The cleanup facilities include three types of mechanical systems, two types of in situ burning systems, and three types of dispersant application systems (vessel, helicopter, and C-130). Each system has a corresponding operating capacity, available number, operational cost, and response time. All the other input data are available upon request.

All the computational studies were performed on an IBM T400 laptop with an Intel 2.53 GHz CPU and 2 GB RAM. DICOPT was used as the MINLP solver. The MILP problems were solved by using CPLEX 12.2 with an optimality tolerance of 10^{-9} . The nonlinear programming subproblems were solved with KNITRO41 with an optimality tolerance of 10^{-6} . We consider a response time span of 76 days in this example. The resulting MINLP problem includes 2,052 discrete variables, 11,482 continuous variables, and 14,006 constraints. We first solve the approximate MILP problem and use its solution as the starting point of solving the MINLP problem. The solution process takes a total of 139 CPU-seconds. We note that the problem becomes “infeasible”, when we solved the MINLP directly without




Figure 3: Optimal length of coastal protection boom

the initialization step.

The results are given in Figures 2 and 3. Figures 2 show the time trajectories of the oil volume throughout the response operations when time span is 76 days. The drop lines are for the collocation points in the finite elements. We can see a trend from these figures that the volume of remaining oil first increases from Day 0 to Day 42 and then decreases, because the oil was being released at a constant rate to the sea surface before Day 42. These figures show that dispersant application is usually the most favorable cleanup method because of its flexibility in various weather conditions, although it might not be available in the early stage of the response. Skimming is also a major cleanup method, because the total amount of chemical dispersant used is constrained by regulation and mechanical cleanup can gain credit from oil recovery. Figure 3 shows the length of coastal protection booms deployed in the three staging areas when the response time span is 76 days. We can see that the three staging areas start to deploy booms from Day 8, Day 21, and Day 19, respectively. The different starting days are due to the different boom deployment rates and different locations of the staging areas. S1 deploys the booms first, because it has shortest distance to the oil spill site; Although S2 is closer to the spill site than S3, S3 starts to deploy the booms earlier than S2, because S3 requires much longer booms to protect the coast and longer deployment time.

5. Model Extensions

This work can be extended to deal with the uncertainty involved in the model. There are two potential approaches that can effectively tackle this issue. One is to extend the MIDO model to its stochastic version and to explicitly consider these uncertain parameters; the other is to apply a real time MIDO formulation. A reviewer also suggested to minimize response time, t_f , which provides an indirect measure of the ecological damage. To study the trade-offs between these two objectives, one could develop a multi-objective optimization approach.

6. Acknowledgment

This research is supported by the U.S. Department of Energy under contract DE-AC02-06CH11357 and through grant DE-FG02-05ER25694.

REFERENCES

- [1] Allgor R. and Barton P. Mixed-integer dynamic optimization. *Computers & Chemical Engineering* 21:S451-S456, 1997.
- [2] Bansal V., Sakizlis V., Ross R., Perkins J., and Pistikopoulos E. New algorithms for mixed-integer dynamic optimization. *Computers & Chemical Engineering* 27:647-668, 2003.
- [3] Brebbia C.A. Oil spill modeling and processes. WIT Press, UK, 2001.
- [4] Buchanan I. and Hurford N. Methods for predicting the physical changes in oil spilt at sea. *Oil & Chemical Pollution* 4:311-328, 1988.
- [5] Chachuat B, Singer A, and Barton P. Global mixed-integer dynamic optimization. *AIChE Journal* 51:2235-2253, 2005.
- [6] Fay J.A. The spread of oil slicks on a calm sea. In *Oil on the sea*, Houtt D.-P., Ed. Plenum Press, New York, pp. 53-63, 1969.
- [7] Fingas M. The basics of oil spill cleanup. Lewis, New York, 2001.
- [8] Mackay D., Buist I.A., Mascarenhas R., Paterson S. Oil spill processes and models. Environment Canada Manuscript Report No 8. EE-8, Ottawa, Ontario, 1980.

- [9] Michel J., Adams E.E., Addassi Y., Copeland T., Greeley M., James B., Mcgee B., Mitchelmore C., Onishi Y., Payne J., Salt D., and Wrenn B. Oil spill dispersants: efficacy and effects. National Academies Press, Washington, DC, 2005.
- [10] NOAA. *Oil spill case histories 1967-1991: summaries of significant U.S. and international spills*, Seattle, Washington, 1992.
- [11] Ornitz B. and Champ M. Oil spills first principles: prevention and best response. Elsevier, Netherlands, 2003.
- [12] Reed M. The physical fates component of the natural resource damage assessment model system. *Oil and Chemical Pollution* 5:99-123, 1989.
- [13] Reed M., Johansen I., Brandvik P.J., Daling P., Alun L., Fiocco R., Mackay D., and Prentki R. Oil spill modeling towards the close of the 20th century: overview of the state of the art. *Spill Science & Technology Bulletin* 5:3-16, 1999.
- [14] Sager S., Bock H.G., and Diehl M. The integer approximation error in mixed-integer optimal control. *Mathematical Programming* to appear.
- [15] Sebastiao P. and Sores C.G. Modeling the fate of oil spills at sea. *Spill Science & Technology Bulletin*. 2:121-131, 1995.
- [16] Segel, L.A. Segel and Slemrod M. The Quasi-Steady-State Assumption: A Case Study in Perturbation. *SIAM Review*, 31(3):446-477, 1989.
- [17] Stiver W. and Mackay D. Evaporation rate of spills of hydrocarbons and petroleum mixtures. *Environmental Science & Technology* 18:834-840, 1984.
- [18] Ventikos N.P., Vergetis E., Psaraftis H.N., and Triantafyllou G. A high-level synthesis of oil spill response equipment and countermeasures. *Journal of Hazardous Materials* 107:51-58, 2004.
- [19] Wilhelm W.E., and Srinivasa A.V. Prescribing tactical response for oil spill clean up operations. *Management Science* 43:386-402, 1997.
- [20] <http://www.restorethegulf.gov/>.
- [21] You F. and Leyffer S. Mixed-Integer Dynamic Optimization for Oil Spill Response Planning with Integration of A Dynamic Oil Weathering Model. *AIChE Journal* 2010, Submitted. Preprint ANL/MCS-P1794-1010, Mathematics and Computer Science Division, Argonne National Laboratory, 2010.
- [22] Zhong Z. and You F. Oil spill response planning with consideration of physicochemical evolution of the oil slick: A multiobjective optimization approach.
- Computers & Chemical Engineering* 2010, Submitted. Preprint ANL/MCS-P1786-0810, Mathematics and Computer Science Division, Argonne National Laboratory, 2010.
-

Bulletin

SIAM Optimization 2011

The SIAM Conference on Optimization will be held in Darmstadt, Germany, May 16–19, 2011. We have an excellent slate of invited speakers:

- Thomas Bortfeld, Harvard Medical School, USA.
- Thomas F. Coleman, University of Waterloo, Canada.
- Dorit Simona Hochbaum, University of Southern California, USA.
- Jon Lee, IBM TJ Watson Research Center, USA.
- Claudia Sagastizábal, CEPTEL, Brazil.
- Defeng Sun, National University of Singapore, Singapore.
- Fredi Tröltzsch, Technische Universität Berlin, Germany.
- Stephen Wright, University of Wisconsin, USA.

The conference will co-locate with the *SIAM Workshop on Combinatorial Scientific Computing (CSC11)*, May 19–21, 2011. CSC11 addresses combinatorial challenges in computational science and engineering. The workshop includes themes on parallel computing, high-performance algorithms, sparse matrix computations, combinatorial problems in optimization, automatic differentiation, mesh generation, computational biology, and combinatorial matrix theory. For more information, see <http://www.siam.org/meetings/csc11/>.

For those still undecided on whether to come, check out <http://www.darmstaedter.de>, the Darmstädter Privatbrauerei!

SIAG/OPT Elections

The following candidates have been elected to three-year terms as officers of our SIAG from 2011–2013:

- Chair: *Michael Todd*, Cornell.
- Vice Chair: *Mihai Anitescu*, Argonne National Laboratory.
- Program Director: *Miguel Anjos*, Polytechnique, Montréal.
- Secretary: *Marina Epelman*, University of Michigan.

Congratulations to all four! The running of the SIAG will be in excellent hands.

Comments from the Editor

Whilst this issue may be light on content (only one article), we decided to push it out in order to announce the SIAG/OPT election results, and to advertise the upcoming SIAM Optimization conference in Darmstadt. The paper presented here is almost entirely the brainchild and work of one of Argonne's talented postdocs, who took up the challenge to model oil spill response as an optimization problem. The paper provides an overview of this complex model that is also available in GAMS format upon request.

We have ambitious plans for larger and more substantive issues for next year. However, as always, we welcome suggestions and articles. So, if you can think of an area that should receive a special issue, please contact me!

Finally, the placement of the editor's comments before the chairman's column should not be regarded as a slight to Michael, but rather as evidence of my own inability to effectively control page-breaks in L^AT_EX.

Sven Leyffer, Editor

Mathematics and Computer Science Division

Argonne National Laboratory

Argonne, IL 60439, USA

leyffer@mcs.anl.gov

<http://www.mcs.anl.gov/~leyffer/>

Chairman's Column

This is the last column that I will write as Chair of SIAG/OPT before handing over the reins to the capable hands of Mike Todd for the next three years. I am grateful to him for agreeing to serve, and also to the new officers Mihai Anitescu, Miguel Anjos and Marina Epelman. Many thanks also to Hande Benson, Robert Freund, William Hager, Michael Hintermueller and Kim-Chuan Toh for their willingness to participate in the election process.

On a local front, we are excited by the migration of the NEOS server and guide to Wisconsin. Both of these sites are now being hosted at the Wisconsin Institutes of Discovery, a new interdisciplinary research facility in Madison, in which Optimization is one of the five principal research areas. We are attempting to provide a more powerful compute service (for which we would welcome your optimization problem input and testing), and aim to update the information in the guide to be more reflective of where our field now stands. The new urls are:

<http://www.neos-server.org/>

and

<http://www.neos-guide.org/>

respectively. We would very much welcome volunteers to provide additional content to this wiki, and pointers to extra information and resources that casual browsers of this site might find interesting, as well as the opportunity to host more solvers for new and existing problem formats. Please mail support@neos-server.org any suggestions or new content. I would be remiss if I did not thank all of the many contributors to the NEOS outreach effort, but especially the entire NEOS team at Argonne and Northwestern University for their inspired guidance and tenacity in making NEOS an effective gateway into our discipline from the wider reaches of the Internet. We are also pleased to announce the addition

of Gurobi to our class of LP and MIP solvers, joining a collection of techniques and codes that span our discipline.

We had a huge increase in the number of nominations for the SIAG Optimization prize this year and I thank both the committee (in advance) for their review and assessment, and all those who took time to nominate papers. The results will be announced at the next SIAG Optimization meeting in Darmstadt.

I believe that the number of submissions for that meeting (both minisymposia and contributed talks) was astounding. The job of arranging these into the program and facilitating extra space to accommodate them has been a challenge. I thank Steve Vavasis, Stefan Ulbrich and the staff at SIAM for their skills and patience in getting this done. I am very much looking forward to the meeting and know that I will see many of you in Darmstadt, Germany between May 16 and 19.

I am trusting that if you are reading this you have already renewed your membership of the SIAG - if not please make this a top priority! I am hopeful that the next decade will prove to be a defining one for optimization - our capabilities to solve problems of critical interest to science and industry has grown enormously over this past decade - let's make it significantly impact these and other areas in the next 10 years!

Finally, I would like to thank Yinyu Ye, Tom McCormick and Steve Vavasis and the SIAM staff for their help and support over the past three years, and to our intrepid newsletter editor, Sven Leyffer for his ability to engineer a newsletter "on demand". It has been a pleasure serving with each and every one of them.

Michael C. Ferris, SIAG/OPT Chair
 Computer Sciences Department
 University of Wisconsin-Madison
 1210 West Dayton Street,
 Madison, WI 53706
 USA
ferris@cs.wisc.edu
<http://www.cs.wisc.edu/~ferris>
